



Operating & Stationary Units, HEIGHT

CALL SIZE (HEIGHT)	HEIGHT IN INCHES
2-0	23½
2-8	31½
3-0	35½
3-6	41½
4-0	47½
4-1	48½
4-4	51½
5-0	59½
5-2	61½

Single Operating Units, WIDTH

CALL SIZE (WIDTH)	2-6	3-0	3-6	4-0	4-1	5-0	6-0
SINGLE	29½	35½	41½	47½	48½	59½	71½

Transom Units, HEIGHT

CALL SIZE (HEIGHT)	HEIGHT IN INCHES
1-2	13½
1-4	15½
1-8	19½
2-0	23 ½

Triple Operating Units, WIDTH

CALL SIZE (WIDTH)	6-0 3E	7-0 3E	8-0 3E	6-0 3P	7-0 3P	8-0 3P
TRIPLE	71½	83½	95½	71½	83½	95½

Operating Units

Call Size	Clear Opening Width	Clear Opening Height	Clear Opening S.F.	Daylight Opening S.F.
VBSL2620	10.500	17.688	1.29	2.6
28	10.500	25.688	1.87	3.8
30	10.500	29.688	2.16	4.4
36	10.500	35.688	2.60	5.3
38	10.500	37.688	2.75	5.6
40	10.500	41.688	3.04	6.2
41	10.500	42.688	3.11	6.3
44	10.500	45.688	3.33	6.8
50	10.500	53.688	3.91	8.0
52	10.500	55.688	4.06	8.3
VBSL3020	13.500	17.688	1.66	3.4
28	13.500	25.688	2.41	4.9
30	13.500	29.688	2.78	5.6
36	13.500	35.688	3.35	6.8
38	13.500	37.688	3.53	7.2
40	13.500	41.688	3.91	7.9
41	13.500	42.688	4.00	8.1
44	13.500	45.688	4.28	8.7
50	13.500	53.688	5.03	10.2
52	13.500	55.688	5.22	10.6
VBSL3620	16.500	17.688	2.03	4.1
28	16.500	25.688	2.94	5.9
30	16.500	29.688	3.40	6.9
36	16.500	35.688	4.09	8.3
38	16.500	37.688	4.32	8.7
40	16.500	41.688	4.78	9.6
41	16.500	42.688	4.89	9.9
44	16.500	45.688	5.24	10.6
50	16.500	53.688	6.15	12.4
52	16.500	55.688	6.38	12.9

Call Size	Clear Opening Width	Clear Opening Height	Clear Opening S.F.	Daylight Opening S.F.
VBSL4020	19.500	17.688	2.40	4.8
28	19.500	25.688	3.48	7.0
30	19.500	29.688	4.02	8.1
36	19.500	35.688	4.83	9.7
38	19.500	37.688	5.10	10.3
40	19.500	41.688	5.65	11.4
41	19.500	42.688	5.78	11.7
44	19.500	45.688	6.19	12.5
50	19.500	53.688	7.27	14.7
52	19.500	55.688	7.54	15.1
VBSL4120	20.000	17.688	2.46	4.9
28	20.000	25.688	3.57	7.2
30	20.000	29.688	4.12	8.3
36	20.000	35.688	4.96	10.0
38	20.000	37.688	5.23	10.5
40	20.000	41.688	5.79	11.7
41	20.000	42.688	5.93	12.0
44	20.000	45.688	6.35	12.8
50	20.000	53.688	7.46	15.0
52	20.000	55.688	7.73	15.6
VBSL5020	25.500	17.688	3.13	6.3
28	25.500	25.688	4.55	9.1
30	25.500	29.688	5.26	10.6
36	25.500	35.688	6.32	12.7
38	25.500	37.688	6.67	13.4
40	25.500	41.688	7.38	14.9
41	25.500	42.688	7.56	15.2
44	25.500	45.688	8.09	16.3
50	25.500	53.688	9.51	19.1
52	25.500	55.688	9.86	19.8

Call Size	Clear Opening Width	Clear Opening Height	Clear Opening S.F.	Daylight Opening S.F.
VBSL6020	31.500	17.688	3.87	7.8
28	31.500	25.688	5.62	11.6
30	31.500	29.688	6.49	13.0
36	31.500	35.688	7.81	15.7
38	31.500	37.688	8.24	16.6
40	31.500	41.688	9.12	18.3
41	31.500	42.688	9.34	18.8
44	31.500	45.688	9.99	20.1
50	31.500	53.688	11.74	23.6
52	31.500	55.688	12.18	24.5

NOTE: Units listed in red satisfy BOCA egress requirements. Check with your local code official to confirm egress requirements in your area.

Triple Operating Units

Call Size	Clear Opening Width	Clear Opening Height	Clear Opening S.F.	Daylight Opening S.F.
VBSL6020-3E	20.650	17.688	2.50	7.5
28-3E	20.650	25.688	3.70	10.9
30-3E	20.650	29.688	4.30	12.6
36-3E	20.650	35.688	5.10	15.2
38-3E	20.650	37.688	5.40	16.0
40-3E	20.650	41.688	6.00	17.7
41-3E	20.650	42.688	6.10	18.1
44-3E	20.650	45.688	6.60	19.4
50-3E	20.650	53.688	7.70	22.8
52-3E	20.650	55.688	8.00	23.7
VBSL6020-3P	13.964	17.688	1.70	7.5
28-3P	13.964	25.688	2.50	10.9
30-3P	13.964	29.688	2.90	12.6
36-3P	13.964	35.688	3.50	15.2
38-3P	13.964	37.688	3.70	16.1
40-3P	13.964	41.688	4.00	17.8
41-3P	13.964	42.688	4.10	18.2
44-3P	13.964	45.688	4.40	19.5
50-3P	13.964	53.688	5.20	22.9
52-3P	13.964	55.688	5.40	23.7

Call Size	Clear Opening Width	Clear Opening Height	Clear Opening S.F.	Daylight Opening S.F.
VBSL7020-3E	24.650	17.688	3.00	9.0
28-3E	24.650	25.688	4.40	13.0
30-3E	24.650	29.688	5.10	15.1
36-3E	24.650	35.688	6.10	18.1
38-3E	24.650	37.688	6.50	19.2
40-3E	24.650	41.688	7.10	21.2
41-3E	24.650	42.688	7.30	21.7
44-3E	24.650	45.688	7.80	23.2
50-3E	24.650	53.688	9.20	27.3
52-3E	24.650	55.688	9.50	28.3
VBSL7020-3P	16.964	17.688	2.10	9.0
28-3P	16.964	25.688	3.00	13.1
30-3P	16.964	29.688	3.50	15.1
36-3P	16.964	35.688	4.20	18.2
38-3P	16.964	37.688	4.40	19.2
40-3P	16.964	41.688	4.90	21.2
41-3P	16.964	42.688	5.00	21.7
44-3P	16.964	45.688	5.40	23.3
50-3P	16.964	53.688	6.30	27.3
52-3P	16.964	55.688	6.60	28.4

Call Size	Clear Opening Width	Clear Opening Height	Clear Opening S.F.	Daylight Opening S.F.
VBSL8020-3E	28.650	17.688	3.50	10.4
28-3E	28.650	25.688	5.10	15.2
30-3E	28.650	29.688	5.90	17.6
36-3E	28.650	35.688	7.10	21.1
38-3E	28.650	37.688	7.50	22.3
40-3E	28.650	41.688	8.30	24.7
41-3E	28.650	42.688	8.50	25.3
44-3E	28.650	45.688	9.10	27.0
50-3E	28.650	53.688	10.70	31.8
52-3E	28.650	55.688	11.10	33.0
VBSL8020-3P	19.964	17.688	2.50	10.5
28-3P	19.964	25.688	3.60	15.2
30-3P	19.964	29.688	4.10	17.6
36-3P	19.964	35.688	4.90	21.1
38-3P	19.964	37.688	5.20	22.3
40-3P	19.964	41.688	5.80	24.7
41-3P	19.964	42.688	5.90	25.3
44-3P	19.964	45.688	6.30	27.1
50-3P	19.964	53.688	7.40	31.8
52-3P	19.964	55.688	7.70	33.0