



WINDOWS & DOORS®



## MW JEFFERSON® 300 DOUBLE HUNG

### CARRYING ON THE TRADITION

*Historically accurate, the Jefferson 300 Double Hung Wood Window provides a look that harkens back 100 years. But make no mistake, this window has features planted firmly in the 21st century. Like a low-maintenance cellular PVC exterior, fully welded all-vinyl sash that tilt-in, energy-efficient glass and multiple exterior casing options. At MW, we're also carrying on our long tradition of service to the builder, with on-time delivery, on-site field support and a commitment to make sure your windows keep you on schedule.*



MW JEFFERSON®  
**300 DOUBLE HUNG**



**STANDARD FEATURES**

- ❖ Low-maintenance cellular PVC exterior components ready to accept acrylic latex paints
- ❖ 4-9/16" jamba eliminate need for drywall work; custom jamb extensions to 8-9/16"
- ❖ Classic double hung design with traditional brick mould complements an array of architectural styles
- ❖ Paint-free all-vinyl sash fully welded at the corners
- ❖ Energy-efficient Warm Edge Insulated Glass
- ❖ Low-maintenance cellular PVC exterior brick mould
- ❖ Both sashes tilt in and remove for safe and easy cleaning of exterior glass
- ❖ Balances counter-balanced with quiet, adjustable springs for smooth up and down action
- ❖ Bulb weather-stripping at top, bottom and check rails for efficient performance and smooth, easy openings and closings

**OPTIONS**

**Glass Options:** Low-E, Low-E/Argon, Tinted, Low-E Tinted, Tempered and Obscure

**Exterior Casings:** 180 Brick Mould (standard), 3-1/4" Williamsburg, 3-1/2" Flat, 5-1/2" Flat or 4-1/2" Wide Back Band, Bull Sill Nose

**Balance Options:** Compression standard, Easy-Tilt optional

**Grille Options:** Grille-between-the-glass (GBG) in flat 5/8", 7/8" styles, sculptured 5/8" and 1" contour styles; classic muntin bar appearance with 1-1/4" simulated-divided-lite (SDL)

**Product Configuration:** Twins, Side Lites, Stationary, Combinations, Bays & Bows, Circle Heads, Quarter Circles, Ellipticals, Transoms, True Radius, Arches and a wide variety of architectural shapes

**TESTING & PERFORMANCE DATA**

Tested in accordance with ASTM standards; rated in accordance with International Residential Code; and witnessed by an independent AAMA accredited lab.

**NFRC Thermal Performance:**

	U Value†	R Value	SHGC**	VLT**
3/4" Clear	0.47	2.13	0.60	0.62
3/4" Low-E	0.34	2.94	0.35	0.53
3/4" Low-E/Argon	0.30	3.33	0.35	0.53

\* Solar Heat Gain Coefficient    \*\* Visible Light Transmission



CSM-JF3DH013006 REV. C



**WINDOWS & DOORS®**